

Fiber Optics Distribution Box

TE-ODB-4

Overview

TE Platform TE-ODB-4 optical distribution box is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

Features

- Wet-proof, water-proof, dust-proof, anti-aging
- Easy installations: Ready for wall mount – installation kits provided
- Space saving: Double-layer design for easier installation and maintenances
- Easy installations: Ready for wall mount – installation kits provided.
- Protection level up to IP66
- Cabinet can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses.
- Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
- Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor installation, easy maintenance.
- Loaded With 4 Adapter SC/UPC Simplex.



Dimensions and Capability

Adapter Capacity	LC Duplex	SC Simplex
	4	4
Dimensions (W*H*D)	210mm*135mm*40mm	
Number of Cable Entrance	1 uncut cable entrance: 10-16.5mm	
Number of Cable Exit	Up to 4 Drop Cables	
Weight	0.32 KG	
Optional Accessories	Adapters, Pigtails, Heat Shrink Tubes, Optical Splitter	
Installation	Wall-Mounted or Pole-Mounting	

Operation Conditions

Temperature	-40°C -- 60°C
Humidity	95% above 40°C
Air Pressure	62kPa – 101kPa

Shipping Information

Package Contents	Fiber optics distribution box, 1 unit; Keys for lock, 2 keys; Wall mount accessories, 1 set
Material	Carton box
Lead Time	15 working days normally

Part Details

